

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM DAVE@OLINPUMP.COM



SPECIFICATIONS 15 55/75 CONCRETE PUMP



LEG MOUNTED UNIT SHOWN W/ NOISE REDUCTION ENCLOSURE

	15 55	15 75
OUTPUT: cmh /cyh	45/60	60/80
DELIVERY PRESSURE: bar/psi		77/1100
DELIVERY CYLINDER: mm/inch		178/7
STROKE: mm/inch	610/24	914/36
STROKES/MINUTE:	50	45
ENGINE POWER: kw/hp	75/100	98/130
HOPPER CAPACITY: l/gal		300/79
OUTLET: mm/inch		127/5
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC	
HYDRAULIC CAPACITY: l/gal		338/89
WEIGHT: kg/lbs	2574/5720	2632/5850
LENGTH: cm/inch		445/175
WIDTH:		178/70
HEIGHT:		208/82

The midsize range of Olin's S-Tube pumps not only provides a choice of size and price, but also features the same great hopper inlet and cleanout characteristics, ease in wear part access, simple electric/hydraulic circuitry, and the smoothest flow at the working end of the delivery system.



**GRout – SHOTCRETE – CONCRETE – PRESSURE GROUTING
AND SPECIAL APPLICATION PUMPS**