

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM INFO@OLINPUMP.COM



SPECIFICATIONS 580/95 1/2" MINUS PUMP



	5 80	5 95
OUTPUT: cmh /cyh	61/80	72/95
DELIVERY PRESSURE: bar/psi	76/1100	76/1100
DELIVERY CYLINDER: mm/inch		178/7
STROKE: mm/inch	610/24	914/36
STROKES/MINUTE:	54	47
ENGINE POWER: kw/hp	82/108	95/125
HOPPER CAPACITY: l/gal		189/50
OUTLET: mm/inch		100/4
OIL COOLER		YES
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC	
HYDRAULIC CAPACITY: l/gal		338/89
WEIGHT: kg/lbs	2495/5500	2644/5830
LENGTH: cm/inch		445/175
WIDTH:		178/70
HEIGHT:		208/80

The 5 80 & 95's 7" delivery cylinders combined with the Millennium Series manifold, handle both course and high sack structural 1/2" mixes, making them the perfect choice for residential, commercial, and large slurry backfill jobs.

* All OLIN Ball Valve pumps feature delivery system pressure release valve standard.



CONCRETE - GROUT - SHOTCRETE

