

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM DAVE@OLINPUMP.COM



SPECIFICATIONS 15 30 CONCRETE PUMP



OUTPUT: cmh/cyh	28/35
DELIVERY PRESSURE: bar/psi	53/750
DELIVERY CYLINDER: mm/inch	127/5
STROKE: mm/inch	610/24
STROKES/MINUTE:	60
ENGINE POWER: kw/hp	36/48
HOPPER CAPACITY: l/gal	299/79
OUTLET: mm/inch	127/5
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC
HYDRAULIC CAPACITY: l/gal	318/84
WEIGHT: kg/lbs	2035/4490
LENGTH: cm/inch	386/162
WIDTH:	178/70
HEIGHT:	208/82

Fixed displacement, single source hydraulics make the smallest, most economical of Olin's S-Tube Stationary Pumps even more simple to operate. With all the same great features of the larger pumps, simplicity of design, high efficiency, maintenance friendliness, great value, and after sale support unequalled in the industry.



**GROUT – SHOTCRETE – CONCRETE – PRESSURE GROUTING
AND SPECIAL APPLICATION PUMPS**