

# OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

[WWW.OLINPUMP.COM](http://WWW.OLINPUMP.COM) DAVE@OLINPUMP.COM



## SPECIFICATIONS 15 35/45 CONCRETE PUMP



CAGE MOUNTED UNIT SHOWN W/ NOISE REDUCTION ENCLOSURE

	15 35	15 45
OUTPUT: cmh /cyh	28/38	37/50
DELIVERY PRESSURE: bar/psi	63/900	77/1100
DELIVERY CYLINDER: mm/inch	127/5	152/6
STROKE: mm/inch		610/24
STROKES/MINUTE:	63	57
ENGINE POWER: kw/hp	49/65	59/78
HOPPER CAPACITY: l/gal		299/79
OUTLET: mm/inch		127/5
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC	
HYDRAULIC CAPACITY: l/gal		318/84
WEIGHT: kg/lbs	2109/4650	2159/4760
LENGTH: cm/inch		411/162
WIDTH:		178/70
HEIGHT:		208/82

The small end of Olin's S-Tube Stationary Pumps offer all the same great features of the larger pumps; simplicity of design, high efficiency, maintenance friendliness, great value, and after sale support that is unequalled in the industry.



**GROUT – SHOTCRETE – CONCRETE – PRESSURE GROUTING  
AND SPECIAL APPLICATION PUMPS**