

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM DAVE@OLINPUMP.COM



SPECIFICATIONS 5 140/170CA 1/2" MINUS FOUNDATION PUMP



	5 140CA	5 170CA
OUTPUT: cmh /cyh	105/140	127/170
DELIVERY PRESSURE: bar/psi		63/900
DELIVERY CYLINDER: mm/inch		200/8
STROKE: mm/inch		1371/54
STROKES/MINUTE:	53	65
ENGINE POWER: kw/hp	150/200	187/250
HOPPER CAPACITY: l/gal		340/90
OUTLET: mm/inch		100/4
OIL COOLER		YES
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC	
HYDRAULIC CAPACITY: l/gal		376/99
WEIGHT: kg/lbs	3400/7495	3629/8000
LENGTH: cm/inch		518/204
WIDTH:		178/70
HEIGHT:		208/80

The 5 140 & 170's 8" delivery cylinders combined with the Millennium Series manifold, deliver the most efficiency of any auger cast pile pump on the market.

No other pumps perform anywhere close to the OLINPUMP grout pumps. Efficiency, output, low maintenance and smooth delivery with no surge, make it the highest value pump available.

*All OLIN Ball Valve pumps feature delivery system pressure release valve standard.



**GROUT – SHOTCRETE – CONCRETE – PRESSURE GROUTING
AND SPECIAL APPLICATION PUMPS**